

Press Technical Data Sheet



The Lawton Press range is available in sizes from 15-54mm. Perfect for heat-free installations in potable water, heating, and cooling applications, this innovative product comes with an unbeatable 30-year warranty, showcasing our commitment to quality and reliability.



Lawton Press Fittings	15-54mm
Applications	Potable water, Heating and Cooling
Market Segmentation	Domestic and Commercial
Approvals	REG 4 and WRAS

Materials:	Copper and DZR brass (CW602N)
Sealing:	EPDM O-ring
Press Configuration:	M-profile
Maximum Operating Pressure (Liquid):	16 bar (0-100°C)
Maximum Operating Pressure (Negative Pressure):	>0.2 bar (0-100°C)
Dimensions:	See webpage
Product Marking:	Size, LTC logo, EN1254
Warranty:	30 years (See website for T&Cs)
Electrical Continuity:	Yes
Thread Specification:	Male - ISO 7/EN10226-1
	Female - BS EN ISO 228
Assembly Instructions:	See webpage
Features:	Leak before press O-ring
	Leak before press indicator (black)
	No solder required
	No hot works permits needed
Standard:	EN 1254-7



Copper Tube Compatibility:

Outer Diameter	0.7mm Wall	0.9mm	1.0mm	1.2mm	1.5mm
15mm	R250		R250		
	R290		R290		
22mm		R250		R250	
		R290		R290	
28mm		R250		R250	
		R290		R290	
35mm			R290	R250	R290
				R290	
42mm			R290	R250	R290
				R290	
54mm				R290	

Copper Tube to BS EN 1057 - Tempers are R250 (half hard, can be bent) or R290 (hard, cannot be bent).

Dissimilar metals:

Installations containing mixed metals are generally to be avoided. Metals that are not close to each other on the galvanic scale can corrode when connected directly together.

If dissimilar metals are required in the same system, we recommend the Water Regulations Guide is adhered to.

Distance between fittings:

It is recommended to maintain a minimum distance between each fitting, to account for the deformation of the tube profile when pressed. This also applies to localised annealing.

F = Clearance between fitting ends.



Tube Size	Minimum Clearance F (mm)
15mm	5
22mm	5
28mm	5
35mm	10
42mm	15
54mm	20

For more details, please refer to our website or contact us by email at technical@lawtontubes.co.uk